

407672

MONTHLY STATUS AND PROGRESS REPORTS FOR MAY 1953

This document contains restricted information as defined in the Atomic Energy Act of 1946. Its transmission or the disclosure of its content in any form to any unauthorized person is prohibited.

Extract

DEPARTMENT OF ENERGY DECLASSIFICATION REVIEW	
SINGLE REVIEW AUTHORIZED BY: <i>Denegallo 11/2/94</i>	DETERMINATION (CIRCLE NUMBER(S)) 1. CLASSIFICATION RETAINED 2. CLASSIFICATION CHANGED TO: 3. CONTAINS NO DOE CLASSIFIED INFO
REVIEWER (ADD): NAME: <i>HR Schmidt</i>	4. COORDINATE WITH: 5. CLASSIFICATION CANCELLED 6. CLASSIFIED INFO BRACKETED
DATE: <i>12/7/94</i>	7. OTHER (SPECIFY): <i>Cover and pp</i>

25-28 only

U.S. ATOMIC ENERGY COMMISSION

Washington, D. C.

Issued June 17, 1953

OPEN	ENTERED
By _____	Date _____
Entered in Copy _____	Date _____
By _____	Date _____
<input checked="" type="checkbox"/> Not Authorized for Public Release	
By _____	Date _____

US DOE ARCHIVES

326 U.S. ATOMIC ENERGY COMMISSION

Collection *1342*

Box *1*

Folder *7*

This document consists of No. *1* of *1* copies, Series *11342-1-7-1*

~~SECRET~~
~~SECURITY INFORMATION~~

1342-1-7-1

94H DOT 1792
WASH-108

EXTRANEOUS MATERIAL DELETED

EXTRANEOUS MATERIAL DELETED

VI - BIOLOGY AND MEDICINEResearch Activities

Effects of X rays on frog retina. The University of California Radiation Laboratory has completed a study on the effect of X rays on animal retina. Particularly the visual response to small doses of X rays was examined. Measurements on the bullfrog were made to determine the threshold intensity needed to elicit a light stimulus and the adaptation and recovery after small doses of X rays. It was found that electrical response could be measured on the retina after 0.6 roentgens, that during exposure to X rays the sensitivity to light was reduced, and that recovery of the retina after an X ray stimulus was slower than after a light stimulus. This recovery phenomenon indicates that the effect is to a large extent reversible and that the phenomenon is one of the smallest reversible responses which has been observed with penetrating radiations.

Biological synthesis of fatty acids. Research at the University of California at Los Angeles includes a project on the mechanism of metabolism in animals with respect to fatty acids in the body. It has been demonstrated for the first time that an "essential" fatty acid can be synthesized in the animal body. This "essential" acid--arachidonic--contains 20 carbon atoms. Synthesis was accomplished from carboxyl labeled acetate and a compound containing 18 carbon atoms. Further studies will be undertaken to elucidate the physiological significance of this reaction.

Biological effects of radiation. At Los Alamos Scientific Laboratory, experiments have been undertaken to determine the biological effects of total-body X radiation in mice. Pretreatment of mice with p-aminopropiophenone (an agent producing a pronounced hypoxia) or glutathione, exerted a marked protective effect against total-body X radiation. A negligible degree of protection was found when mice so pretreated were exposed to thermal column radiation (thermal neutrons plus gamma contaminant).

It is tentatively suggested that the lack of effect of these agents against thermal column exposure results from the fact that the majority of the ionizations are produced along a short track and that under these conditions certain products produced by the ionization of water can be formed independently of molecular oxygen.

On the basis of the data reported it appears that agents which are protective against one type of ionizing radiation may not be of value against all types and that tissue oxygen tension may play a role in producing the marked differences observed in the relative effectiveness of neutrons and X rays in various tissues.

Radiation effects on mortality. The effects of whole body irradiation of male rats on mortality among their offspring is being studied by the AEC-University of Tennessee research group. Male rats were exposed to 300 roentgens of gamma rays from a cobalt 60 source, or to X rays at 250 kilovolts peak voltage. The irradiated males were subsequently mated to

virgin females. The pregnant females were sacrificed, and it was found that the foetal death rate showed an increase in comparison with non-irradiated controls. The percentage of deaths for each group was:

Control group.....	6.46 per cent
Gamma-ray exposure.....	19.37 per cent
X rays.....	19.92 per cent

After 60 days the same male animals were used in repeating the experiment. The values obtained after sacrifice of the second group of pregnant females were 7.39 percent for gamma exposure and 8.19 percent for X rays. This result does indicate a period of recovery and may be due to dominant lethal mutations induced during exposure in the more mature testis cells.

Research in photosynthesis. At Oak Ridge National Laboratory, recent information has been reported in connection with the activity of light energy in photosynthesis. It has been known for some time that green plants fluoresce and that the fluorescence is the back reaction from excited chlorophyll which has absorbed light. When the lights are turned off, the fluorescence ceases in less than 10^{-7} seconds and is felt to represent the reversibility of the first step in light absorption by chlorophyll—namely, the formation of excited chlorophyll. Investigations have shown that there is also a much weaker light emission which lasts for some seconds after the plant is placed in the dark. The emission spectrum of this delayed weak light has been shown to be the same as the fluorescence of chlorophyll. The data indicate that the delayed light emission represents the reversal of the first several steps in photosynthesis, the light ultimately coming only from the reversal of the first step.

Radiation Instruments

Special electronics development. The steering committee for the electronics development program held a meeting at Argonne National Laboratory on May 14, 15, 1953. In the light of technical developments and the increasing demand for special electronic requirements of various AEC installations, recommendations were made to accelerate studies in (a) basic research on the phenomena of photoelectric emission; (b) research development of new photoelectric and secondary emissive surfaces; (c) improvement of photomultiplier transit spread characteristics; (d) development of large photocathode multiplier tubes up to 30 inches and 36 inches in diameter; and (e) model shop fabrication of test quantities of tubes developed under the program. Research projects will be undertaken with Notre Dame University, the Radio Corporation of America, and the Allen B. DuMont Laboratories.

Review of standardization problems. The accelerated pace of instrument development in the atomic energy field inevitably introduces a number of problems in standardization requirements. The Radiation Instruments Branch maintains close liaison with the many organizations of government and private industry and serves as representative or advisory member

on numerous committees which formulate recommendations to further standardization of basic instrumentation and component parts pertinent to technical operations.

In the nuclear instrumentation field, one of the major problems lies in the production of various types of electrical cable connectors which serve similar functions on manufacturers' equipment. The Radio-Television Manufacturers' Association subcommittee on nuclear instrumentation recently discussed the frequency of use of various connector-type cables in AEC laboratory-built nuclear measurement equipment. A tabulation was given which showed that two particular types of connectors (identified as the IPC 27000 and IPC type HN series) were in predominant use for high-voltage service; for low-voltage circuits the IPC 4500 was used. The subcommittee recommended that the standard type of high-voltage connector on commercial nuclear measurement equipment would be of one type--namely, the type-HN series connector. The type UHF (IPC 11875) connector with teflon insert was selected as the standard type for use in low-voltage circuits. Although such problems may not appear significant, the recommendation represents a step forward. The efficacy of technical operations is dependent on the flexibility of interconnecting equipment, and standardization procedures are important in reducing costs and labor.

In an effort to prepare the way for future developments in this field, meetings are held periodically with the Office of Basic Instrumentation of the National Bureau of Standards to coordinate plans for research studies. Membership is made up of the sponsoring agencies such as AEC and the Department of Defense, who are principal consumers of special instruments and devices necessary in technical operations. This program is designed to establish a cohesiveness of purpose and effort in basic instrumentation research projects at the various laboratories of interested groups, and to eliminate unnecessary duplications of effort. This work is of benefit to all fields of science to which problems of instrumentation are related. Recommendations for the coming year emphasize: studies on critical surveys of currently used instruments or instrumentation techniques; theoretical or experimental evaluation of new applications of physical principles in measurement and control; and theoretical analysis in various fields of measurement, control and handling of data. (End of UNCLASSIFIED section.)

General ~~RESTRICTED SECURITY INFORMATION~~

Fall-out phenomena, Washington, D. C. Following the atomic detonation of May 25 at Nevada Proving Ground, the trajectory of the path of the atomic cloud for the 18,000-foot level showed that it passed over Washington, D. C., on May 26. On the same day, a hailshower in the northwest section of the city produced hailstones, some of which were two to three inches in diameter. The radioactivity in the air recorded at the Naval Research Laboratory at the time of the hailshower was the highest yet noted here, 6×10^{-3} microcuries per cubic meter averaged over 24 hours. The activity remained in the air in significant amounts for about five hours. The standard maximum permissible concentration is 1.0

~~CONFIDENTIAL - SECURITY INFORMATION~~

microcuries per cubic meter averaged over 24 hours.

The hailstones were collected and melted down to examine the water for radioactivity. The activity measured on the third day after detonation by the Naval Research Laboratory was 2×10^{-4} microcuries per cubic centimeter, and by the Division of Biology and Medicine, 3.2×10^{-5} and 1.6×10^{-5} microcuries per cubic centimeter. These values may be compared to the maximum permissible concentration of 5×10^{-3} microcuries per cubic centimeter for drinking water, which is based on the assumptions that all of the water intake will be from the same source and consumed at this concentration continuously. Of course, the activity decays rapidly according to well-established principles.

Data have also been obtained by the Naval Research Laboratory showing that activity in the center region of the hailstones was approximately five times greater than in the peripheral region. (End of section.)

[REDACTED]

[REDACTED]

VII - PRODUCTION

Feed Materials

Uranium production. The feed material operations continued without incident. Although the production of UO_3 and UF_4 was less than scheduled, the production of machined slugs remained on schedule.

UF_6 feed preparation. Uranium hexafluoride production decreased 2.4 percent from the previous month. Maintenance work requirements, principally in the fluorine generators, largely accounted for the decrease. Production of uranium tetrafluoride increased 22.2 percent above that in April. This substantial increase resulted from the use of a recently developed experimental vertical hydrofluorinator and the use of a quantity of uranium trioxide received directly from Hanford. This material proved to have a higher reactivity than material which is purified at Harshaw. Test quantities of UO_3 having impurities in excess of current specifications are being shipped directly to Oak Ridge to determine the maximum level of impurities which may be tolerated in the UF_6 feed plant. The bulk of Hanford's UO_3 continues to be shipped to Harshaw for purification.

The use of more reactive material results in increased output of tetrafluoride of high purity, which in turn requires less fluorine for conversion to the hexafluoride. Since the fluorine supply is a controlling

EXTRANEOUS MATERIAL DELETED

EXTRANEOUS MATERIAL DELETED